



SPECIFICATIONS FOR FIXED-MOUNTED INFRARED TEMPERATURE SENSOR

ENVIRO-THERM™ (4000)

OPTIMIZED FOR MEASURING PLANT-FOLIAGE SURFACE TEMPERATURE

TEMPERATURE MEASUREMENT

SCALE RANGE:	-10°C TO 100°C
RESOLUTION:	0.1°C
ACCURACY:	±0.3°C FROM -10°C TO 50°C & ±0.5°C OVER 50°C & UNDER 100°C
REPEATABILITY:	±0.1°C
TEMPERATURE:	ALL FUNCTIONS IN °C
NOISE EFFECTIVE TEMPERATURE:	±0.2°C

OPTICAL CONSIDERATIONS

SPECTRAL PASS BAND:	8 < WAVELENGTHS < 14 MICRONS
SIGHTING:	LINE-OF-SIGHT
FIELD OF VIEW:	STANDARD: 10° OPTIONAL: 5° AND 2° AVAILABLE AT ADDITIONAL COST

OPERATING CONDITIONS

OPERATING ENVIRONMENT:	-40°C TO 100°C UP TO 99% RELATIVE HUMIDITY, NON-CONDENSING
STORAGE TEMPERATURE:	SAME AS OPERATING ENVIRONMENT TEMPERATURE
SEALING:	ONE SOLID BLOCK OF PLASTIC HERMETICALLY SEALED WITHIN A CASE. DOUBLY WATERPROOF. CONNECTOR SYSTEM EXCEEDS COASTGUARD SPECIFICATIONS FOR WATER TIGHTNESS (CFR 46 PART 110.20). SALT SPRAY: MIL-STD202 Method 101D

ELECTRICAL INTERFACE

POWER REQUIREMENTS:	4.8V TO 15V DC. 90 VAC - 250 VAC, 50/60 HZ
OUTPUT SIGNAL:	STANDARD: ANALOG: MILLIVOLT (10mV/°C) DIGITAL: I ² C FORMAT OPTIONAL: TYPE K THERMOCOUPLE

GENERAL

RESPONSE TIME:	.75 SECOND
EMISSIVITY COMPENSATION:	PRESET TO PLANT FOLIAGE EMISSIVITY (0.98)
SKY RADIATION DETECTION/ CORRECTION	STANDARD SKY-SPY™ SYSTEM FOR DETECTION & CORRECTION OF UNWANTED SKY REFLECTION
OPERATING DISTANCE:	2 CM TO 300 METERS
DIMENSIONS:	1" DIAMETER BY 2.5" LENGTH
WARRANTY:	ONE-YEAR LIMITED WARRANTY ON PARTS AND LABOR

EVEREST INTERSCIENCE HAS A POLICY OF CONTINUED DESIGN UPGRADE. THEREFORE, WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE.

EVEREST INTERSCIENCE INC

2888 English Road, Chino Hills, CA 91709 USA

Tel: (714) 478-1616 • Fax: (909) 590-7467

E-mail: Info@EverestInterscience.com

Website: EverestInterscience.com